

PVC COATED FABRIC

JUM·PhiPher

DATA SHEET

技术参数

12oz

Testing Method

Standard Width 门幅	137cm -- 320 cm 54 inch -- 126 inch	
Base Fabric 基布	100%PES 1000Dx1000D 20x20	DIN EN ISO 2060
Total Weight 总克重	410 g/m ² 12 OZ/YD ²	DIN EN ISO 2286-2 BS 3424 Method 5A
Breaking Strength Warp 抗拉强度（经向）	2300 N/5cm 518 LBS/2inch	DIN 53 354 BS 3424 Method FS 5100
Breaking Strength Weft 抗拉强度（纬向）	2300 N/5cm 518 LBS/2inch	DIN 53 354 BS 3424 Method FS 5100
Tear Strength Warp 撕裂强度（经向）	280 N 63 LBS	DIN 53 363 BS 3424 Method FS 5134
Tear Strength Weft 撕裂强度（纬向）	260 N 58.5 LBS	DIN 53 363 BS 3424 Method FS 5134
Adhesion 剥离强度	100 N/5cm 22.5 LBS/2inch	DIN 53 357 BS 3424 Method 9B FS 5970
Temperature resistance	-20°C/+70°C	DIN EN 1876-2 BS 3424 Method 10 FS 5874
Light Fastness(except white) 色牢度（白色除外）	7-8	DIN EN ISO 877 BS 3424 Method 15
Flammability 防火	B1,B2 PASS PASS	DIN 75200 NFPA-701 CPAI-84 / ASTM E-84

All our technical characteristics are indicative

以上参数如有变动，恕不另行通知。