

PVC COATED FABRIC

JUM Co., Ltd

DATA SHEET

技术参数

JU1861M

Testing Method

Standard Width 门幅	137 cm -- 320cm 54 inch -- 126 inch	
Base Fabric 基布	100%PES 1000Dx1300D 18x17, Twistec	DIN EN ISO 2060
Total Weight 总克重	610 g/m ² 18 OZ/YD ²	DIN EN ISO 2286-2 BS 3424 Method 5A
Breaking Strength Warp 抗拉强度 (经向)	2400 N/5cm 540 LBS/2inch	DIN 53 354 BS 3424 Method FS 5100
Breaking Strength Weft 抗拉强度 (纬向)	2400 N/5cm 540 LBS/2inch	DIN 53 354 BS 3424 Method FS 5100
Tear Strength Warp 撕裂强度 (经向)	450 N 101 LBS	DIN 53 363 BS 3424 Method FS 5134
Tear Strength Weft 撕裂强度 (纬向)	400 N 90 LBS	DIN 53 363 BS 3424 Method FS 5134
Adhesion 剥离强度	95 N/5cm 21 LBS/2inch	DIN 53 357 BS 3424 Method 9B FS 5970
Temperature resistance	-20°C/+70°C	DIN EN 1876-2 BS 3424 Method 10 FS 5874
Light Fastness(except white) 色牢度 (白色除外)	7-8	DIN EN ISO 877 BS 3424 Method 15
Flammability 防火	B1,B2 PASS PASS	DIN 75200 NFPA-701 CPAI-84 / ASTM E-84

All our technical characteristics are indicative

以上参数如有变动，恕不另行通知。