

PVC COATED FABRIC

JUM·PhiPher

DATA SHEET

技术参数

J11861C

Testing Method

Standard Width 门幅	150cm 59 inch, Cape embossing	
Base Fabric 基布	100%PES 1000Dx1000D 20x20	DIN EN ISO 2060
Total Weight 总克重	610 g/m ² 18 OZ/YD ²	DIN EN ISO 2286-2 BS 3424 Method 5A
Breaking Strength Warp 抗拉强度（经向）	2200 N/5cm 495 LBS/2inch	DIN 53 354 BS 3424 Method FS 5100
Breaking Strength Weft 抗拉强度（纬向）	2200 N/5cm 495 LBS/2inch	DIN 53 354 BS 3424 Method FS 5100
Tear Strength Warp 撕裂强度（经向）	320 N 72 LBS	DIN 53 363 BS 3424 Method FS 5134
Tear Strength Weft 撕裂强度（纬向）	300 N 67.5 LBS	DIN 53 363 BS 3424 Method FS 5134
Adhesion 剥离强度	110 N/5cm 25 LBS/2inch	DIN 53 357 BS 3424 Method 9B FS 5970
Temperature resistance	-20°C/+70°C	DIN EN 1876-2 BS 3424 Method 10 FS 5874
Light Fastness(except white) 色牢度（白色除外）	7-8	DIN EN ISO 877 BS 3424 Method 15
Flammability 防火	B1,B2 PASS M1,M2	DIN 75200 NFPA-701 N F 92507

All our technical characteristics are indicative

以上参数如有变动，恕不另行通知。